



\\AUBERGINE



\\OXFORD



\\CAMEL



\\CHOCOLATE



\\MOCHA



\\VANILLA



\\CASHMERE



\\LEAF



\\SAGE



\\CHERRY



\\OXBLOOD



\\BURNT ORANGE



\\BLACK



FABRIC CUTS

BUCKDENRANGE

FABRICUS

TECHNICAL SPECIFICATIONS

Fabric Composition:	1% PU 64% PVC 11% Cotton 24% Polyester
Coated Width:	140 cm
Waterproof:	Hydrostatic head BS3424> 1 metre
Flame Retardant:	BS5852 Ignition Source 0, 1 & 5 (Crib 5)
Martindale Abrasion:	end point > 100,000 cycles)

CLEANING & MAINTENANCE

Clean regularly with a damp soapy cloth, then rinse with cold water and wipe dry with a clean cloth. It is important to avoid saturating the surface with water. Microfibre cloths are particularly effective. Stains caused by body fluids should be wiped off immediately using cold water. Stains caused by tea, coffee and foodstuffs should be wiped off immediately using warm water.

SOLVENTS, SYNTHETIC DETERGENTS, ABRASIVES, AEROSOL SPRAYS AND POLISHES MUST NOT BE USED AS THEY MAY DAMAGE THE SURFACE OF THE FABRIC.

COLOUR MATCHING

Whilst we strive to achieve consistency of colour, shade variations can occur during the manufacturing process of fabric batches. Where an exact colour match is required a stock sample must be requested prior to confirmation of order.

SAMPLING

Larger samples available on request.
Please contact our sales office for specific requirements.

FABRICUS LTD
Unit 2, Heathfield Industrial Estate,
Elland, West Yorkshire HX5 9AE

Tel: +44 (0) 1422 373554
Fax: +44 (0) 1422 372154

Email: sales@fabricus.co.uk
Web: www.fabricus.co.uk

FABRICUS